Amendments to the Specification:

Please amend the specification as follows:

[0015] The base cover 32 comprises an inner face [[323]] 320 and an outer face 322. A plurality of key buttons (not labeled) protrudes from a lower portion of the inner face [[323]] 320. A rectangular display 34 for showing messages or images is defined on an upper portion of the inner face [[323]] 320, adjacent to the key buttons. The base cover 32 receives a main circuit board (not shown) for controlling operations of the mobile phone 3. The main circuit board and other structures of the base cover 32 are similar to those in traditional foldable mobile phones. A shutter button 325 protrudes from a right side (not labeled) of the base cover 32, ~~which~~ and is electrically connected with the main circuit board.

[0018] To take pictures of the user, the mobile phone 3 is used in the closed position, as shown in FIG. 1. The user confronts the camera 36, and can preview the image shown on the display 34 through the vision window 304, since the camera 36 and the display 34 face in the same direction. When the user is satisfied with the image, he or she can press the shutter button 325, and the photograph is thus taken. When the user wants to take pictures of objects other than himself or herself, he or she can turn the flip cover 30 upwardly so that the mobile phone 3 is in the open position, as shown in FIG. 3. Then, the camera 36 points toward objects which are to be photographed, and the user can directly preview an image on the display 34. Satisfactory pictures or images are thus obtained using the mobile phone 3.

PAGE 3/15 * RCVD AT 10/12/2005 6:12:28 PM [Eastern Daylight Time] * SVR:USPTO-EFXRF-6/29 * DNIS:2738300 * CSID:408 919 8353 * DURATION (mm-ss):05-22